

fuhrmeister



K ü h l g e r ä t e
Serie RAM **S**mart Edelstahl

Die Kühlgeräte-Serie RAM Smart Edelstahl ist für den Chemie-, Pharma-, Food and Beverage- und den geschützten Outdoor-Bereich mit hohen Umgebungstemperaturen bis zu +55°C konzipiert. Serienmäßig ist ein elektronischer Temperaturregler mit Türkontaktschleife und potentialfreiem Störmeldekontakt sowie eine integrierte Kondensatverdunstung verbaut. Durch die Flachbauweise, die getrennten Kreisläufe (IP54/IP34) und Kühlleistungen von 1420W bis 3850W eignet sich diese Serie für ein breites Anwendungsfeld.



- LED Easy-Control
- Schnellmontage durch aufgeschäumte Dichtung
- Integrierte Kondensatverdunstung
- Großer Abstand zwischen Luftein- und austritt für optimierte Luftführung
- Anbaugeräte nur 400mm breit

The cooling units series RAM Smart Inox are specially developed for chemical-, pharmacy-, food & beverage-industry and finally for the protected outdoor usage with high temperatures up to +55°C. An electronic temperature controller including a door-switch control and alarm-signal output and an integrated condensate dissipator is built in as standard. The slim sized housing, the separated air-circuits (IP54/IP34.) and cooling power from 1420W up to 3850W make this series suitable to a wide range of applications.



- LED Easy-Control
- Quick mounting due to applied seal
- Integrated condensate dissipator
- Large distance between air in- and outlet for optimized air flow
- Side-mounting units with only 400mm width

| Serie RAM Smart Series RAM Smart | Tu Ta | Nutzkühlleistung Cooling Power | Spannung Voltage | Abmessungen Dimensions |
|-------------------------------------|----------|-----------------------------------|------------------------|---------------------------|
| Type/model | bis °C | W (L35L35) | V, Hz | B x H x T (mm) |
| RIKLMFU15021SOT | 55 | 1420 | 230, 1~, 50/60 | 400 x 1500 x 190 |
| RIKLMFU15021SIT | 55 | 1420 | 230, 1~, 50/60 | 490 x 1570 x 190 |
| RIKLMFU15042SOT | 55 | 1420 | 400/440/460, 2~, 50/60 | 400 x 1500 x 190 |
| RIKLMFU15042SIT | 55 | 1420 | 400/440/460, 2~, 50/60 | 490 x 1570 x 190 |
| RIKLMFU20021SOT | 55 | 1960 | 230, 1~, 50/60 | 400 x 1650 x 220 |
| RIKLMFU20021SIT | 55 | 1960 | 230, 1~, 50/60 | 490 x 1720 x 220 |
| RIKLMFU20042SOT | 55 | 1960 | 400/440/460, 2~, 50/60 | 400 x 1650 x 220 |
| RIKLMFU20042SIT | 55 | 1960 | 400/440/460, 2~, 50/60 | 490 x 1720 x 220 |
| RIKLMFU30021SOT | 55 | 2800 | 230, 1~, 50 | 400 x 1650 x 220 |
| RIKLMFU30021SIT | 55 | 2800 | 230, 1~, 50 | 490 x 1720 x 220 |
| RIKLMFU30043SOT | 55 | 2800 | 400/460, 3~, 50/60 | 400 x 1650 x 220 |
| RIKLMFU30043SIT | 55 | 2800 | 400/460, 3~, 50/60 | 490 x 1720 x 220 |
| RIKLMFU40043SOT | 50 | 3850 | 400/460, 3~, 50/60 | 400 x 1650 x 220 |

Andere Spannungen auf Anfrage

