

# fuhrmeister



K ü h l g e r ä t e  
Serie RAM **S**mart

Die Kühlgeräte der Serie RAM Smart sind auf Grund ihrer flachen Bauweise, der zwei voneinander getrennten Kreisläufe (IP54/IP34) und einem weiten Kühlleistungsspektrum von 1420W bis 3850W für alle gängigen, industriellen Anforderungen geeignet. Serienmäßig ist ein elektronischer Temperaturregler mit Türkontaktschleife und potentialfreiem Störmeldekontakt verbaut. Die komplette Serie verfügt über eine integrierte Kondensatverdunstung. Alle Geräte sind auch mit einer Inox-Haube erhältlich.

The cooling units of series RAM Smart are suitable for the most industrial applications, based on their slim size, the two separated air-circuits (IP54/IP34) for preventing dust insertion and a wide range of cooling power from 1420W up to 3850W. An electronic temperature controller including a door-switch control and alarm-signal output is built in as standard. The whole series is equipped with integrated condensate dissipators. All units are also available with Inox-covers.



- LED Easy-Control
- Schnellmontage durch aufgeschäumte Dichtung
- Integrierte Kondensatverdunstung
- Großer Abstand zwischen Luftein- und austritt für optimierte Luftführung
- Anbaugeräte nur 400mm breit

- LED Easy-Control
- Quick mounting due to applied seal
- Integrated condensate dissipator
- Large distance between air in- and outlet for optimized air flow
- Side-mounting units with only 400mm width

Serie RAM Smart Series RAM Smart Type/model	Tu Ta bis °C	Nutzkühlleistung Cooling Power W (L35-L35)	Spannung Voltage V, Hz	Abmessungen Dimensions BxHxT (mm)
R5KLMFU15021SOT	55	1420	230, 1~, 50/60	400 x 1500 x 190
R5KLMFU15021SIT	55	1420	230, 1~, 50/60	490 x 1570 x 190
R5KLMFU15042SOT	55	1420	400/440/460, 2~, 50/60	400 x 1500 x 190
R5KLMFU15042SIT	55	1420	400/440/460, 2~, 50/60	490 x 1570 x 190
R5KLMFU20021SOT	55	1960	230, 1~, 50/60	400 x 1650 x 220
R5KLMFU20021SIT	55	1960	230, 1~, 50/60	490 x 1720 x 220
R5KLMFU20042SOT	55	1960	400/440/460, 2~, 50/60	400 x 1650 x 220
R5KLMFU20042SIT	55	1960	400/440/460, 2~, 50/60	490 x 1720 x 220
R5KLMFU30021SOT	55	2800	230, 1~, 50	400 x 1650 x 220
R5KLMFU30021SIT	55	2800	230, 1~, 50	490 x 1720 x 220
R5KLMFU30043SOT	55	2800	400/460, 3~, 50/60	400 x 1650 x 220
R5KLMFU30043SIT	55	2800	400/460, 3~, 50/60	490 x 1720 x 220
R5KLMFU40043SOT	50	3850	400/460, 3~, 50/60	400 x 1650 x 220



Andere Spannungen auf Anfrage

