



Kühlgeräte / Cooling units  
Serie Smart Edelstahl

Die Serie Smart Edelstahl ist besonders für die Chemie-, Pharma-, Food and Beverage-Industrie oder für den geschützten Outdoor-Bereich geeignet. Die Gehäuse sind komplett aus Edelstahl gefertigt und mit einem elektronischen Thermostat inklusive Türkontaktschleife und Störmelkontakt ausgestattet. Außerdem ist die gesamte Serie durchgängig **cRU<sub>US</sub>** zertifiziert. Die Geräte verfügen über 2 voneinander getrennte Kreisläufe mit einer schrankseitigen Schutzart IP54.

The series Smart Edelstahl is especially suitable for the chemical-, pharmacy-, or food & beverage-industry or for the protected outdoor use. The units housing are completely made of inox material and are equipped with an electronic thermostat including door-switch-control and alarm signal. Additionally the whole series is **cRU<sub>US</sub>** certified. Of course all units are equipped with two separated air-circuits to prevent intrusion of dust with protection rate on the cabinets side of IP54.



- Gehäuse aus AISI 304 (1.4301)
- Sehr flache Bauform
- Geeignet für An- oder Einbau
- **cRU<sub>US</sub>** Zertifizierung
- Alle Leistungsgrößen für 120VAC/60Hz lieferbar

- Housing made of AISI 304 (1.4301)
- Very slim sizing
- Suitable for side or internal mounting
- **cRU<sub>US</sub>** certification
- All sizes available for 120VAC/60Hz

Serie Smart Edelstahl	Type Model	Tu Ta	Nutzkühlleistung Cooling Power	Spannung Voltage	Abmessungen Dimensions
Bestell-Nr./Order-No.		bis °C	W (L35L35)	V, Hz	B x H x T (mm)
20.INSX.AC03.0901	FC-INS-AC03	50	320	230, 1~, 50/60	270 x 520 x 110
20.INSX.ACH4.0901	FC-INS-ACH4	50	400	230, 1~, 50/60	520 x 340 x 110
20.INSX.AC05.0901	FC-INS-AC05	50	500	230, 1~, 50/60	320 x 600 x 110
20.INSX.AC08.0901	FC-INS-AC08	55	820	230, 1~, 50/60	395 x 980 x 145
20.INSX.AC08.0907	FC-INS-AC08	55	820	380-415, 3~, 50 / 400-460, 3~, 60	395 x 980 x 145
20.INSX.AC11.0901	FC-INS-AC11	55	1100	230, 1~, 50/60	395 x 1250 x 145
20.INSX.AC11.0907	FC-INS-AC11	55	1100	380-415, 3~, 50 / 400-460, 3~, 60	395 x 1250 x 145
20.INSX.AC15.0901	FC-INS-AC15	55	1500	230, 1~, 50/60	395 x 1550 x 145
20.INSX.AC15.0907	FC-INS-AC15	55	1500	380-415, 3~, 50 / 400-460, 3~, 60	395 x 1550 x 145

